

# **Guideline related to the use of a 3<sup>rd</sup> party router on the Proximus residential network**

## Table of contents

Table of contents	2
1 Terminology	3
2 Introduction	3
3 Basic Setup	3
<b>3.1</b> Requirements	3
<b>3.2</b> Configuration	4
3.2.1 VLAN Tagging:	4
3.2.2 IP acquisition from the network:	4
<b>3.3</b> Use of an external modem	4

## 1 Terminology

- “must” or “shall” is used to indicate a mandatory element.
- “should” is used to express a strong recommendation.

## 2 Introduction

**Edpnet does not manage the fixed internet network mentioned, but offers its services through the Proximus network.**

This document is provided as a reference guide for Equipment Manufacturers and End Users within the framework of the Decision of 26 September 2023 regarding the identification of the network termination point for broadband services. The information contained herein pertains to Proximus' network specifications.

The purpose of this document is to furnish insights into the current state of information and network specifications, serving as a guideline for third-party routers that might be deployed by end-users on the Proximus residential network.

### Scope:

- This document provides details on the configuration requirements for third-party routers when interfacing with the Proximus residential network.
- It outlines the standards that must be adhered to by the third-party routers to ensure proper interoperability with the Proximus network.

### Limitations:

- This document does not constitute a comprehensive router specification but specifically addresses essential points crucial for achieving interoperability with the Proximus residential network.
- The document does not cover the characteristics necessary for a modem to establish a connection to the physical line. For modem-specific requirements, please refer to the modem specifications provided separately:
  - DSL Modem Specification: “PXS\_VDSLspecs”
  - ONT Specification: “PXSEndUser\_ONTspecs\_v03”

### Usage Considerations:

- The information presented in this document is based on the current state of information and network specifications, subject to change. It is recommended to regularly check for updates and revisions.

**Disclaimer:** The guidelines outlined in this document are provided on an "as-is" basis. While every effort has been made to ensure accuracy, Proximus shall not be liable for any direct, indirect, incidental, consequential, or special damages arising out of the use of this information.

## 3 Basic Setup

### 3.1 Requirements

The following features must be supported by the router:

- VLAN Tagging on the WAN interface
- SLAAC (rfc 4862)
- IPv6 prefix delegation
- ARP (rfc 826)

The router must allow for the configurations described in the following paragraphs to be set by the end user.

## 3.2 Configuration

### 3.2.1 VLAN Tagging:

Proximus residential lines make use of a single VLAN (VLAN 10) for connectivity towards the network. The router must thus be configured so that its WAN interface encapsulates traffic in VLAN 10.

### 3.2.2 IP acquisition from the network:

IPv4 acquisition is done via PPPoE.

## 3.3 Use of an external modem

If the router is connected to an external modem (e.g., DSL modem or ONT) by means of an Ethernet cable, the end user should make sure that the external modem is bridging traffic at the OSI Layer 2 level (this is the case for Proximus modems).

If the connection between the modem and the router is found to be unstable (packet loss), this might be due to one of the following elements:

- The Ethernet cable isn't properly plugged in.
- The Ethernet cable isn't adapted to the negotiated throughput. Make sure an Ethernet cable of the proper category is used (CAT 5E is good for connections up to 1 Gbps, CAT 6A or CAT 7 is to be used for connections up to 10 Gbps).
- Energy Efficient Ethernet is enabled.